

DK82HU-N

HighSecLabs Dual Head 8-Port 4K30 UHD HDMI KVM Switch with sUSB

| DVI | C-KVM



DK82HU-N is a dual head 8-port, 4K30 UHD HDMI KVM switch. It enables users to share peripherals - keyboard, video, mouse, audio, and USB between eight different networks/computers. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer

FEATURES

4K30 UHD Resolution - Supports resolutions up to 3840×2160

Extended/Duplicated Display Support - Enables switching keyboard, mouse and up to 2 displays (either extended or duplicated) between computers

Multi Display Support - Change to KM mode to enable switching keyboard and mouse control between computers, when each computer is connected to up to 4 displays (either extended or duplicated)

Smooth Switching Between Computers (Virtual Display Technology) - Automatically switch all peripheral control from one computer to another by dragging the cursor between each computer's display border

Versatile and Flexible - Configurable as a KVM switch (default) for sharing a display, keyboard and mouse between connected computers, or KM switch for sharing keyboard and mouse and simultaneously working on multiple computers connected to separate displays

Copy & Paste - Transfer text and files between all the computers that are connected to the KVM switch (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or context-menu commands

Super Speed USB 3.0 Port - Transfer data and files between peripherals and computers USB 3.0 Super Speed rates through the KVM switch USB 3.0 ports

Express USB Charging - Rapidly charge USB devices connected to the high-power USB ports Freeze USB - Assign the USB port to a specific computer while switching the keyboard, video, mouse and audi peripherals between other computers. Useful when a USB device such as a disk-on-key must remain mapped to a certain computer, while the user is working on another computer

Freeze Audio - Assign the audio port to a specific computer while switching the keyboard, video, mouse and USB peripherals between other computers. Useful for scenarios where a user has to listen to audio originating from one computer while working on another computer



TECHNICAL SPECIFICATIONS

Console Ports 2 HDMI connector; 2 USB-A connectors for keyboard and mouse; 3 USB-A 3.0

connectors for USB devices;1 3.5mm mini jack for unbalanced stereo audio;1

RJ-45 connector for control (RDC)

Computer Ports 16 HDMI connectors;8 USB-B connectors for keyboard and mouse;8 USB-B 3.0

connectors for USB devices;8 3.5mm mini jacks for unbalanced stereo audio

Max Resolution 4K30 UHD (3840X2160)

Power Consumption 35W max

AC Input 100 to 240V AC

Power Type External

Operating 32° to $104^{\circ}F$ (0° to $40^{\circ}C$)

Temperature

•

Storage Temperature -4° to 140°F (-20° to 60°C)

Humidity 0-80% RH, non-condensing

Humidity 0-80% RH, non-condensing

Supported OS Windows, Linux, Mac

Product Certification CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

Product Life-cycle 10 years

Product Dimensions 44.00cm x 20.20cm x 6.20cm (17.32" x 7.95" x 2.44") W, D, H

Product Weight 2.9kg (6.4lbs) approx

Shipping Dimensions 52.50cm x 27.50cm x 11.00cm (20.67" x 10.83" x 4.33") W, D, H

Shipping Weight 3.6kg (7.9lbs) approx

