

VIA Campus²

4K30 Wireless Presentation & Collaboration for Education, Training or Any Meeting Environment | HDMI | Microphone - 3.5/6.5mm | Ethernet - RJ-45 | 4K/30 UHD



VIA Campus² is a wireless presentation and collaboration solution that makes it easier to get actual work done during meetings. With any laptop or mobile device, users can view, edit and comment on documents in real time and record sessions. Kramer's new VIA 4.0 is all about the end user. The new VIA application UI is intuitive, user-friendly and much easier to use. VIA 4.0 enables any user, including guests, to easily and securely connect and automatically disconnect at the end of the session. Meeting participants can display or stream full, uninterrupted video (up to 4K@30Hz) from their device, and even play YouTube® videos in full frame rate.

VIA Campus² can show up to six user screens on a single main display and 12 on two displays. Users can also view the main display on their own device. VIA Campus² features iOS mirroring via AirPlay[™], Windows & Android mirroring via Miracast[™], as well as ChromeBook mirroring. The shared screen sizes are automatically adjusted based on their respective source, and can be resized manually by the user when needed.

VIA Campus² supports 3rd party conferencing and office apps, such as Microsoft Office®, Teams®, SkypeforBusiness®, Zoom®, GoToMeeting®, and WebEx®. The solution can handle any size collaboration or meeting space

FEATURES

3rd party Security Certification

Easy and Effective Wireless Connectivity - Built-in Wi-Fi gives you two setup options for enabling meeting participants to wirelessly join the meeting. After setting a wired connection from your VIA device to your local corporate LAN you can do one of the following: use the built-in VIA Wi-Fi to create a guest network to which participants can connect or use the built-in VIA Wi-Fi as a Miracast receiver

Automatically stops presentation when leaving the room

60fps Streaming Multimedia - Share HD wireless video streaming (using the VIA app Multimedia feature)

One 4K@30 (RGB) HDMI output and one 4K@30 DisplayPort output

Remote Power Control - via a relay port

iOS, Android, Chromebook® and Miracast® Mirroring

Optimized for Video Conferencing - Room devices driver feature enables you to wirelessly select the professional grade camera and AV in your meeting room for your VC calls

Calendar widget on the wallpaper for instant connectivity within one click

3rd Party Web Applications - Run directly from the device without needing to use the application Seamless Live Video Streaming - Stream live content from meeting rooms, classrooms and studios using RTMP/RTMPS to all the leading platforms, like YouTube™, Kaltura™, Panopto™ and more

Room Calendar Integration - Shows the room occupancy schedule on the main display

Internal Web Browser - Open any browser to display content

DHCP Support

Streaming Input for the Internal Media Player

Cloud-Based File Sharing - Drag and drop files to the internal VIA cloud storage (128GB) Whiteboard Support

Control - Give a participant control over a presenter's PC for true collaboration **Chat** - Send an instant message to another user

iCloud®, DropBox®, Google Drive®, OneDrive® Integration

View Main Display - View the main display on your own device

Third-Party App Support - Like Microsoft Office®, SkypeforBusiness®, GoToMeeting® and WebEx® Icon Shortcuts - On the splash page for 3rd party applications

Integrated YouTube Player - Create playlists, share videos or drag and drop any YouTube clip to your VIA app for seamless video playback

Streaming Output - Stream all collaboration activity from the main display to any H.264 decoder

Recording - Record an entire VIA video and audio session to a local video file

Digital Signage - Enables you to display dynamic content and information on the main display when there is no meeting in progress. Use a predefined template or create your own display configuration with up to three frames of content that appear simultaneously. Schedule campaigns (content configurations) to run automatically at specific dates and times

Seamless VSM Integration - With VIA Site Management (VSM) software

Multilingual Support - Experience VIA in your language

Warranty - 3 years on hardware



TECHNICAL SPECIFICATIONS

Ports	2 USB 3.1 Gen 1 (blue): On female USB type-A connectors
	3 USB 2.0 (black): On female USB type-A connectors
	1 LAN: On an RJ-45 connector
	2 Wi-Fi Antennas : On threaded Wi-Fi connectors (for future use) 1 Power Toggle :On a 2-pin terminal block
Inputs	1 Microphone: On a 3.5mm jack
Outputs	1 HDMI: On a female HDMI connector
	1 DisplayPort: On a female DisplayPort connector
	1 Unbalanced Stereo Audio Line Out: On a 3.5mm jack
Video	Max. Resolution DisplayPort Output: 4K@30
	Max. Resolution HDMI Output: 4K@30 (RGB)
	Video Streaming Playback (using Kramer VIA app Multimedia feature): 1080p@60fps
	Web Conferencing Cameras Tested with VIA Versa Feature: Logitech MeetUp, Logitech C270, Logitech BCC950, Logitech C525, Logitech Brio UHD PRO, Logitech C310, Logitech C922, Avaya HC020, Avaya HC050, Huddly GO, Yamaha CS700, Minrray MG100A, Microsoft Livecam HD-3000, TedGem 1080p, Vaddio HuddleSHOT, Yealink UVC80, Bose Videobar VB1, BIAMP Devio SCR-20, BIAMP Devio SCR-25,LUMENS B10U, LUMENS B11U, LUMENS B2U, MAXHUB – UCS10 Yealink UVC30ROOM, Aver CAM340+, Avonic AV-CM44-VCUC-B PTZ, Konftel C50 PTZ
	Video Conferencing Apps Tested with VIA Versa Feature: Skype for Business, Skype, Teams, Zoom, Google Meet, BlueJeans, LifeSize Cloud
	All brand names, product names, and trademarks are the property of their respective owners
Audio	Web Conferencing Audio Devices Tested with VIA Versa Feature: Aver VB432 Speaker (Microphone), Yamaha YVC-330 (Speaker, Microphone, Bluetooth phone gateway), Yamaha YVC-1000 (Speaker, Microphone, Bluetooth phone gateway), Nureva HDL300 (Speaker)
	Integrated High Definition Audio : 5.1 channel
General	Processor: i5-12500t
	Main Memory: 8GB (2 x 4GB DDR4 SDRAM modules)
	Storage: 128GB, solid-state drive
	LAN: Gigabit LAN
	Wireless Communication Intel dual-band wireless 802.11ac — model 3168NGW
Power	Source: 120W power adapter (19V, 6.32A)
	Consumption: Max 5A
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F)
	Storage Temperature: −40° to +70°C (−40° to 158°F)

	Humidity: 10% to 90%, RHL non-condensing
Accessories	Included Power adapter, 2 Wi-Fi antennas
Product Dimensions	21.00cm x 19.00cm x 5.00cm (8.27" x 7.48" x 1.97") W, D, H
Product Weight	1.4kg (3.1lbs) approx
Shipping Dimensions	40.50cm x 29.70cm x 9.00cm (15.94" x 11.69" x 3.54") W, D, H
Shipping Weight	2.8kg (6.1lbs) approx



