

VS-211HDxI

2x1:2 SDI Auto Switcher

| 3G HD-SDI - BNC



The VS-211HDxl is a high-performance automatic switcher for 3G HD-SDI video signals. When configured as a standby switcher, it switches to the secondary input when the primary input is lost

FEATURES

Max. Data Rate - 3Gbps

Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) & 3G HD-SDI (SMPTE 424M)

HDTV Compatible

Control - Contact closure or automatic switching

Automatic Standby Switching - Switches from the secondary input to the primary input when a primary signal is detected

Primary Input - Selectable

Active Input LED Indicators

Compact DigiTOOLS $^{\text{TM}}$ - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: 2 SD/HD/3G HD-SDI video on BNC connectors

OUTPUTS: 2 SD/HD/3G HD-SDI video on BNC connectors

MAX. OUTPUT

LEVEL:

 $800 \text{mVpp} / 75 \Omega$

DATA RATE: Up to 2.97Gbps

CONTROLS: Contact closure remote control, input default selection switch

COUPLING: AC

POWER CONSUMPTION:

5V DC, 400mA

INCLUDED

ACCESSORIES:

Power supply, mounting bracket

Product Dimensions 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions $49.00cm \times 18.60cm \times 58.80cm (19.29" \times 7.32" \times 23.15") W, D, H$

Shipping Weight 0.6kg (1.3lbs) approx

