

TBUS-203xI

Pop-Up Table Mount Multi-Connection Solution



The TBUS-203xl is a furniture-mounted pop-up connection bus that is easily installed into a table or podium top. The TBUS-203xl interface enables you to connect any equipment to systems installed in a room via five single inserts or two dual inserts and one single insert

FEATURES

Pneumatic Lift - Easy opening & closing by pressing down gently on the cover. When not in use, it lowers flush with the table

Power Input - Universal, USA, European and many other worldwide power sockets available Elegant and Rugged Rectangular Design - The sturdy and attractive anodized aluminum enclosure provides maximum connectivity in the smallest possible footprint, and at the same time is cost effective and easy to install

Installation - Requires tools and expertise to cut a 21.2cm x 12.2cm (8.4" x 4.8") rectangular hole in the surface of the furniture. Maximum table thickness is 7.6cm (3")

Note - The power socket module is not included. Purchase the country-specific module separately



TECHNICAL SPECIFICATIONS

PORTS: 5 blank inserts

POWER SOCKET

USA Universal 100-240V AC, 50/60Hz, 5A per outlet; 100-220V AC, 50/60Hz, 5A

ASSEMBLIES: per outle

Germany and EU 100-240V AC, 50/60Hz, 5A per outlet; Belgium and France 100-240V AC, 50/60Hz, 5A per outlet;

Italy 100-240V AC, 50/60Hz, 5A per outlet; Australia 100-240V AC, 50/60Hz, 5A per outlet;

Israel 220V AC, 50/60Hz, 5A per outlet;

South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet;

UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet

FUSE RATING: T 6.3A 250V

OPERATING TEMPERATURE

+5° to +45°C (41° to 113°F)

RANGE:

OPERATING HUMIDITY RANGE: 10 to 90% RHL, non-condensing

STORAGE TEMPERATURE

RANGE:

 -20° to $+70^{\circ}$ C (-4° to 158° F)

STORAGE HUMIDITY 5 to 95% RHL, non-condensing

RANGE:

INCLUDED Cut out metal template

ACCESSORIES:

OPTIONS: Power socket kits, power cord

Product Dimensions 23.00cm x 22.63cm x 17.05cm (9.06" x 8.91" x 6.71") W, D, H

Product Weight 1.5kg (3.3lbs) approx

Shipping Dimensions $46.50cm \times 30.00cm \times 42.50cm (18.31" \times 11.81" \times 16.73") W, D, H$

Shipping Weight 2.0kg (4.5lbs) approx



\cap	NI	\sim 1	ID	ΛTI	\cap	NIS.

TBUS-203XL(B)	Pop-Up Table Mount Multi-Connection Solution; Enclosure - Black Sand Blasted Anodized Aluminum Top
TBUS-203XL(BC)	Pop-Up Table Mount Multi-Connection Solution; Enclosure - Silver Sand Blasted Anodized Aluminum Top