

ZyPer Power Center

Product Number: Z4KPWRCTR12

ZyPer 12V Power Center

ZyPer 12V Power Center for use with up to 8 AVoIP ZyPer Encoder/Decoders (all models). 1 RU. Includes rack ears, eight 3-foot locking 12V DC power cables, AC power cord.

Z4KPWRCTR12



What's in the box?

- 12V Power Center
- Rack Ears
- Eight 3-foot locking 12V Power Cables
- Power Cord

ZyPer Power Center

Product Number: Z4KPWRCTR12

Item	
Output Cables	8 x 3 ft (91.4 cm), locking connectors. Cord Plug: 2.1mm I.D. x 5.5mm O.D., Female
Input Voltage / Frequency	110 ~ 240 V AC / 50 ~ 60 Hz
Power Output Ports	8 x 2.0 mm, 12 V DC
Output Voltage	12 V DC \pm 5 %
Output Current	2.0 A (per port)
Output Current / Power	16 A / 192 W (max.)
Fan	2 x internal, 5200 rpm Current: 0.03 A (ea.); Power: 0.4 W (ea.)
Operating Temperature	32 ~ +113 °F (0 ~ +45 °C)
Storage Temperature	-40 ~ +185 °F (-40 ~ +85 °C)
Operating Humidity	20 ~ 90% RH, non-condensing
Storage Humidity	10 ~ 95% RH, non-condensing
Ambient Noise	43.1 dB(A) continuous (Measured 1M distant, straight in front of unit, 10 degrees offset above horizontal)
Dimensions (not including rack ears)	17.2 in x 6.75 in x 1.75 in
Unit Weight	5.29 lb (2.4 kg)

ENTIRE PRODUCT LINE:

Z4K12GSDIENCC3U	Z4KHDMIENCC3U	Z4KDECC3U
Z4K12GSDIENCC3	Z4KHDMIENCF3U	Z4KDECC3
Z4K12GSDIENCF3U	Z4KHDMIENCF3	Z4KENCC3U
Z4K12GSDIENCF3	Z4KDPDECC3U	Z4KDECF3U
Z4KANLENCC3U	Z4KDPDECC3	Z4KDECF3
Z4KANLENCF3	Z4KDPDECF3U	Z4KENCF3U
Z4KDPENCC3	Z4KDPDECF3	